

SERIE 116C

## 98F

**AVO - Wheel with 30% glass-filled polyamide 6 and steel castor for industry, diameter 100mm ean 27716**

**Material:** 30% glass-filled Polyamide 6

**Core:** Glass-filled polyamide 6

**Application field:** Industry

**Description:**

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

**Product line:** Stainless steel, High temperature, Polyamide

**EAN13:**8018793277167

**EAN5:**27716

**Article code:**05098F01000FN



## Features

**Minimum temperature:** -25

**Maximum temperature:** 120

**Dynamic load capacity:** 120 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore D

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                              |
|-----------------------------|------------------------------|
| Diameter (mm)               | 100                          |
| Band width (mm)             | 30                           |
| Hub width (mm)              | 40                           |
| Hub version                 | Plain bore                   |
| Wheel hole (mm)             | 12                           |
| Bearing seat (mm)           | /                            |
| Dynamic load capacity (DaN) | 120                          |
| Colour                      | Grey                         |
| Material                    | 30% glass-filled Polyamide 6 |
| Box pieces                  | /                            |
| Hardness scale              | Shore D                      |
| Hardness                    | 80                           |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | /          |
| Plate hole spacing (mm)    | /          |
| Plate hole size (mm)       | /          |
| Offset (mm)                | 37         |
| Ground clearance (mm)      | 126        |
| Castor hole (mm)           | 12         |
| Static load capacity (DaN) | 150        |
| Structure                  | Swivel     |
| Version                    | Bolt hole  |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |