

SERIE 116C

## 98B

**AVO - Wheel with 30% glass-filled polyamide 6 and steel castor for industry, diameter 125mm ean 27709**

**Material:** 30% glass-filled Polyamide 6

**Core:** Glass-filled polyamide 6

**Application field:** Industry

**Description:**

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

**Product line:** High temperature, Stainless steel, Polyamide

**EAN13:**8018793277099

**EAN5:**27709

**Article code:**05098B01250FN



## Features

**Minimum temperature:** -25

**Maximum temperature:** 120

**Dynamic load capacity:** 170 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore D

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Grey
Material	30% glass-filled Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	80

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized