

SERIE 116C

98A

AVO - Wheel with 30% glass-filled polyamide 6 and steel castor for industry, diameter 150mm ean 22801

Material: 30% glass-filled Polyamide 6

Core: Glass-filled polyamide 6

Application field: Industry

Description:

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Polyamide, Stainless steel, High temperature

EAN13:8018793228015

EAN5:22801

Article code:05098A01500FN



Features

Minimum temperature: -25

Maximum temperature: 120

Dynamic load capacity: 200 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Grey
Material	30% glass-filled Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	/
Ground clearance (mm)	181
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized