

SERIE 116C

98ANTB

AVO - Wheel with 30% glass-filled polyamide 6 and steel castor for industry, diameter 150mm ean 27696

Material: 30% glass-filled Polyamide 6

Core: Glass-filled polyamide 6

Application field: Industry

Description:

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Stainless steel, High temperature, Polyamide

EAN13:8018793276962 **EAN5:**27696 **Article code:**05098BA0150FN



Features

Minimum temperature: -25

Maximum temperature: 120

Dynamic load capacity: 200 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Grey
Material	30% glass-filled Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized