Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 116C

# **98ANT**

AVO - Wheel with 30% glass-filled polyamide 6 and steel castor for industry, diameter 175mm ean 27691

**Material:** 30% glass-filled Polyamide 6

**Core:** Glass-filled polyamide 6

Application field:

Industry

Description:

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls

Product line: High temperature, Polyamide

**EAN13**:8018793276917 **EAN5**:27691 **Article code**:050980A1750FN



### **Features**

Minimum temperature: -25 Maximum temperature: 120

ximum temperature: 120 Dynamic load capacity: 300 DaN

Rotation: Plain bore Hardness scale: Shore D

Hardness: 80

## **Flooring**

- Asphalt
- ConcreteStoneware

#### Wheel data

Diameter (mm)	175
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	300
Colour	Grey
Material	30% glass-filled Polyamide 6
Box pieces	1
Hardness scale	Shore D
Hardness	80

### Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	208
Castor hole (mm)	1
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	1
Stem type	I
Finishing	Galvanized