

SERIE 116C

98F

AVO - Wheel with 30% glass-filled polyamide 6 and steel castor for industry, diameter 175mm ean 27720

Material: 30% glass-filled Polyamide 6

Core: Glass-filled polyamide 6

Application field: Industry

Description:

Polyamide 6 wheel with 30% fiber glass. Hub on plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

Product line: Stainless steel, High temperature, Polyamide

EAN13:8018793277204

EAN5:27720

Article code:05098F01750FN



Features

Minimum temperature: -25

Maximum temperature: 120

Dynamic load capacity: 300 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|------------------------------|
| Diameter (mm) | 175 |
| Band width (mm) | 50 |
| Hub width (mm) | 58 |
| Hub version | Plain bore |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 300 |
| Colour | Grey |
| Material | 30% glass-filled Polyamide 6 |
| Box pieces | / |
| Hardness scale | Shore D |
| Hardness | 80 |

Support data

| | |
|----------------------------|------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 55 |
| Ground clearance (mm) | 205 |
| Castor hole (mm) | 16 |
| Static load capacity (DaN) | 380 |
| Structure | Swivel |
| Version | Bolt hole |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |