

SERIE 116

# 116

## AVO - Wheel with polyamide 6 for industry, diameter 125mm ean 05558

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Product line:** Stainless steel, Polyamide

**EAN13:** 8018793055581    **EAN5:** 05558    **Article code:** 05116001250CN



## Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 300 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore D    **Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

|                             |              |
|-----------------------------|--------------|
| Diameter (mm)               | 125          |
| Band width (mm)             | 40           |
| Hub width (mm)              | 45           |
| Hub version                 | Ball bearing |
| Wheel hole (mm)             | 15           |
| Bearing seat (mm)           | 35X11        |
| Dynamic load capacity (DaN) | 300          |
| Colour                      | White        |
| Material                    | Polyamide 6  |
| Box pieces                  | /            |
| Hardness scale              | Shore D      |
| Hardness                    | 82           |

## Support data

|                            |   |
|----------------------------|---|
| Plate size (mm)            | / |
| Plate hole spacing (mm)    | / |
| Plate hole size (mm)       | / |
| Offset (mm)                | / |
| Ground clearance (mm)      | / |
| Castor hole (mm)           | / |
| Static load capacity (DaN) | / |
| Structure                  | / |
| Version                    | / |
| Brake                      | / |
| Plain axle                 | / |
| Stem type                  | / |
| Finishing                  | / |