

SERIE 116

116

AVO - Wheel with polyamide 6 for industry, diameter 80mm ean 22966

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Product line: Stainless steel, Polyamide

EAN13:8018793229661 **EAN5:**22966 **Article code:**G5116008024FP



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 55 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	24
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	6
Bearing seat (mm)	/
Dynamic load capacity (DaN)	55
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/