

SERIE 116BU

119ANT-BU

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 100mm ean 26468

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate and front brake. Dust cover ring on the balls.

Product line: Stainless steel, Polyamide

EAN13:8018793264686 **EAN5:**26468 **Article code:**1190A1000CNBU



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 150 DaN

Rotation: Stainless steel ball bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Stainless steel ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	150
Colour	Blue
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel