

SERIE 116BU

# 119ANTB-BU

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 100mm ean 26495

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake. Dust cover ring on the balls.

**Product line:** Stainless steel, Polyamide

**EAN13:**8018793264952    **EAN5:**26495    **Article code:**119BA1000RNBU



## Features

**Minimum temperature:** -25

**Maximum temperature:** 85

**Dynamic load capacity:** 150 DaN

**Rotation:** Stainless steel roller bearing

**Hardness scale:** Shore D

**Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

|                             |                                |
|-----------------------------|--------------------------------|
| Diameter (mm)               | 100                            |
| Band width (mm)             | 30                             |
| Hub width (mm)              | 40                             |
| Hub version                 | Stainless steel roller bearing |
| Wheel hole (mm)             | 12                             |
| Bearing seat (mm)           | /                              |
| Dynamic load capacity (DaN) | 150                            |
| Colour                      | Blue                           |
| Material                    | Polyamide 6                    |
| Box pieces                  | /                              |
| Hardness scale              | Shore D                        |
| Hardness                    | 82                             |

## Support data

|                            |                                           |
|----------------------------|-------------------------------------------|
| Plate size (mm)            | /                                         |
| Plate hole spacing (mm)    | /                                         |
| Plate hole size (mm)       | /                                         |
| Offset (mm)                | 37                                        |
| Ground clearance (mm)      | 126                                       |
| Castor hole (mm)           | /                                         |
| Static load capacity (DaN) | 190                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle with brake                           |
| Brake                      | Front                                     |
| Plain axle                 | 20X50                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | AISI 304 stainless steel                  |