

SERIE 116BU

119A-BU

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 125mm ean 26415

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, fixed.

Product line: Stainless steel, Polyamide

EAN13:8018793264150 **EAN5:**26415 **Article code:**119A01250FNBU



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 200 DaN
Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------|
| Diameter (mm) | 125 |
| Band width (mm) | 40 |
| Hub width (mm) | 50 |
| Hub version | Plain bore |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 200 |
| Colour | Blue |
| Material | Polyamide 6 |
| Box pieces | / |
| Hardness scale | Shore D |
| Hardness | 82 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | 100X085 |
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | / |
| Ground clearance (mm) | 155 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 250 |
| Structure | Fixed |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |