

SERIE 116BU

# 119B-BU

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 125mm ean 26437

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem. Dust cover ring on the balls.

**Product line:** Polyamide, Stainless steel

**EAN13:**8018793264372    **EAN5:**26437    **Article code:**119B01250FNBU



## Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 200 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore D    **Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Blue
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	AISI 304 stainless steel