

SERIE 116N

## 95X

**AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 150mm ean 26690**

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate. Dust cover ring on the balls.

**Product line:** Stainless steel, Polyamide

**EAN13:**8018793266901    **EAN5:**26690    **Article code:**05X95001500RN



## Features

**Minimum temperature:** -25

**Maximum temperature:** 85

**Dynamic load capacity:** 200 DaN

**Rotation:** Stainless steel roller bearing

**Hardness scale:** Shore D

**Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

|                             |                                |
|-----------------------------|--------------------------------|
| Diameter (mm)               | 150                            |
| Band width (mm)             | 40                             |
| Hub width (mm)              | 50                             |
| Hub version                 | Stainless steel roller bearing |
| Wheel hole (mm)             | 15                             |
| Bearing seat (mm)           | /                              |
| Dynamic load capacity (DaN) | 200                            |
| Colour                      | Black                          |
| Material                    | Polyamide 6                    |
| Box pieces                  | /                              |
| Hardness scale              | Shore D                        |
| Hardness                    | 82                             |

## Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | 100X085                  |
| Plate hole spacing (mm)    | 080X060                  |
| Plate hole size (mm)       | 8,5X12                   |
| Offset (mm)                | 45                       |
| Ground clearance (mm)      | 181                      |
| Castor hole (mm)           | /                        |
| Static load capacity (DaN) | 250                      |
| Structure                  | Swivel                   |
| Version                    | Plate                    |
| Brake                      | /                        |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | AISI 304 stainless steel |