

SERIE 116BU

119B-BU

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 160mm ean 26447

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem. Dust cover ring on the balls.

Product line: Stainless steel, Polyamide

EAN13:8018793264471 **EAN5:**26447 **Article code:**119B01600RNBU



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 300 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Stainless steel roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel