

SERIE 116

119ANTB

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 200mm ean 20640

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake. Dust cover ring on the balls.

Product line: Stainless steel, Polyamide

EAN13:8018793206402 **EAN5:**20640 **Article code:**06119BA2000RN



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 300 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|--------------------------------|
| Diameter (mm) | 200 |
| Band width (mm) | 50 |
| Hub width (mm) | 58 |
| Hub version | Stainless steel roller bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 300 |
| Colour | White |
| Material | Polyamide 6 |
| Box pieces | / |
| Hardness scale | Shore D |
| Hardness | 82 |

Support data

| | |
|----------------------------|--|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 55 |
| Ground clearance (mm) | 232 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 380 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Front |
| Plain axle | 22X50 |
| Stem type | Stem(on request threaded stem) Plain axle |
| Finishing | AISI 304 stainless steel |