

SERIE 116

119ANT

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 200mm ean 25769

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Polyamide, Stainless steel

EAN13:8018793257695 **EAN5:**25769 **Article code:**061190A2000CN



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 300 DaN

Rotation: Stainless steel ball bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Stainless steel ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	300
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel