

SERIE 116N

## 95XF

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 200mm ean 26747

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole. Dust cover ring on the balls.

**Product line:** Polyamide, Stainless steel

**EAN13:**8018793267472    **EAN5:**26747    **Article code:**05X95F02000RN



## Features

**Minimum temperature:** -25

**Maximum temperature:** 85

**Dynamic load capacity:** 300 DaN

**Rotation:** Stainless steel roller bearing

**Hardness scale:** Shore D

**Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Stainless steel roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	232
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel