

SERIE 116BU

119ANTB-BU

AVO - Wheels with polyamide 6 with castor aisi 304 stainless steel for industry, diameter 60mm ean 26482

Material: / **Core:** Polyamide 6 **Scope:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled whit central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake. Dust cover ring on the balls.

Product line: Stainless steel, Polyamide

EAN13:8018793264822 **EAN5:**26482 **Article code:**119BA0604FNBU



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 120 DaN
Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	60
Band width (mm)	35
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Blue
Material	/
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	87
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	10X30
Stem type	Stem(on request threaded stem)
Finishing	AISI 304 stainless steel