

SERIE 116

119ANTB

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 80mm ean 17230

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled whit central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake. Dust cover ring on the balls.

Product line: Stainless steel, Polyamide

EAN13:8018793172301 **EAN5:**17230 **Article code:**06119BA0800FN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 150 DaN
Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	105
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel