

SERIE 116G

119FG

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 80mm ean 18268

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole. Dust cover ring on the balls.

Product line: Stainless steel, Polyamide

EAN13:8018793182683 **EAN5:**18268 **Article code:**06119F00800FG



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 150 DaN
Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Green
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	105
Castor hole (mm)	12
Static load capacity (DaN)	190
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel