

SERIE 116X

119F

AVO - Wheels with polyamide 6 with castor aisi 304 stainless steel for industry, diameter 80mm ean 22813

Material: / **Core:** Polyamide 6 **Scope:** Industry

Description:

Polyamide 6 wheel. Hub on stainless steel roller bearings or plain bore. Stainless steel teflon bushing is available on request for mm 80 - 100.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793228138 **EAN5:**22813 **Article code:**06119F00800CN



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 150 DaN

Rotation: Stainless steel ball bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Stainless steel ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	150
Colour	White
Material	/
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	105
Castor hole (mm)	12
Static load capacity (DaN)	150
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel