

SERIE 116BU

119ANTF-BU

AVO - Wheel with polyamide 6 and aisi 304 stainless steel castor for industry, diameter 80mm ean 25794

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole and front brake. Dust cover ring on the balls.

Product line: Stainless steel, Polyamide

EAN13:8018793257947 **EAN5:**25794 **Article code:**06119FA0800RB



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 150 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|--------------------------------|
| Diameter (mm) | 80 |
| Band width (mm) | 30 |
| Hub width (mm) | 40 |
| Hub version | Stainless steel roller bearing |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 150 |
| Colour | Blue |
| Material | Polyamide 6 |
| Box pieces | / |
| Hardness scale | Shore D |
| Hardness | 82 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 37 |
| Ground clearance (mm) | 105 |
| Castor hole (mm) | 12 |
| Static load capacity (DaN) | 190 |
| Structure | Swivel |
| Version | Bolt hole with brake |
| Brake | Front |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |