

SERIE 116

## 319XANT-AVO

AVO - Wheel with polyamide 6 and aisi 316 stainless steel castor for industry, diameter 125mm ean 24167

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled whit central spacer.

**Medium duty castors:**

Made of pressed steel AISI 316, turning on double rim of stainless-steel balls AISI 316, with plate and front brake. Dust cover ring on the balls.

**Product line:** Stainless steel, Polyamide

**EAN13:**8018793241670    **EAN5:**24167    **Article code:**063190A125SFN



### Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 170 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore D    **Hardness:** 82

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

### Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Aisi 316 stainless steel