

SERIE 116BU

118BF-BU

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 100mm ean 26379

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13: 8018793263795 **EAN5:** 26379 **Article code:** 118FB1000CNBU



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 175 DaN
Rotation: Ball bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	175
Colour	Blue
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	36
Ground clearance (mm)	131
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized