**ALDO VALSECCHI S.P.A.**
Via XX Settembre, 107
28883 Gravellona Toce (VB) – Italia

www.avo.it
+39 0323 86 99 11
export@avo.it

SERIE 116BU

# 118BF-BU

## AVO - Wheel with polyamide 6 and steel castor for industry, diameter 125mm ean 26382

**Material:** Polyamide 6 **Core:** Polyamide 6 **Scope:** Industry

**Description:**
Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled whit central spacer.

**Heavy-Duty Castors:**
Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Stainless steel, Polyamide

**EAN13:**8018793263825 **EAN5:**26382 **Article code:**118FB1250CNBU

## Features

**Minimum temperature:** -25 **Maximum temperature:** 85 **Dynamic load capacity:** 300 DaN

**Rotation:** Ball bearing **Hardness scale:** Shore D **Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

| | |
|---|---|
| **Diameter (mm)** | 125 |
| **Band width (mm)** | 40 |
| **Hub width (mm)** | 45 |
| **Hub version** | Ball bearing |
| **Wheel hole (mm)** | 15 |
| **Bearing seat (mm)** | 35X11 |
| **Dynamic load capacity (DaN)** | 300 |
| **Colour** | Blue |
| **Material** | Polyamide 6 |
| **Box pieces** | / |
| **Hardness scale** | Shore D |
| **Hardness** | 82 |

## Support data

| | |
|---|---|
| **Plate size (mm)** | / |
| **Plate hole spacing (mm)** | / |
| **Plate hole size (mm)** | / |
| **Offset (mm)** | 45 |
| **Ground clearance (mm)** | 161 |
| **Castor hole (mm)** | / |
| **Static load capacity (DaN)** | 380 |
| **Structure** | Swivel |
| **Version** | Axle with brake |
| **Brake** | Rear |
| **Plain axle** | 22X50 |
| **Stem type** | Plain axle Stem(on request threaded stem) |
| **Finishing** | Galvanized |