

SERIE 116N

## 95ANTB

**AVO - Wheel with polyamide 6 and steel castor for industry, diameter 125mm ean 26554**

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Stainless steel, Polyamide

**EAN13:**8018793265546    **EAN5:**26554    **Article code:**05095BA1254FN



## Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 170 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore D    **Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

|                             |             |
|-----------------------------|-------------|
| Diameter (mm)               | 125         |
| Band width (mm)             | 40          |
| Hub width (mm)              | 50          |
| Hub version                 | Plain bore  |
| Wheel hole (mm)             | 15          |
| Bearing seat (mm)           | /           |
| Dynamic load capacity (DaN) | 170         |
| Colour                      | Black       |
| Material                    | Polyamide 6 |
| Box pieces                  | /           |
| Hardness scale              | Shore D     |
| Hardness                    | 82          |

## Support data

|                            |                 |
|----------------------------|-----------------|
| Plate size (mm)            | /               |
| Plate hole spacing (mm)    | /               |
| Plate hole size (mm)       | /               |
| Offset (mm)                | 42              |
| Ground clearance (mm)      | 150             |
| Castor hole (mm)           | /               |
| Static load capacity (DaN) | 220             |
| Structure                  | Swivel          |
| Version                    | Axle with brake |
| Brake                      | Front           |
| Plain axle                 | 10X30           |
| Stem type                  | Threaded axle   |
| Finishing                  | Galvanized      |