

SERIE 116

118BISBF

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 150mm ean 05672

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13:8018793056724 **EAN5:**05672 **Article code:**05118SBF150FN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 200 DaN
Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized