

SERIE 116

118

**AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 150mm ean 05760**

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13:8018793057608 **EAN5:**05760 **Article code:**05118001500CN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	35
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	40X12
Dynamic load capacity (DaN)	400
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	50
Ground clearance (mm)	189
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized