

SERIE 116

118BISANTF

AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 150mm ean 15733

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: Polyamide, Stainless steel

EAN13:8018793157339 **EAN5:**15733 **Article code:**05118SFA151RN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 130 DaN
Rotation: Roller bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	130
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	12
Static load capacity (DaN)	170
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized