

SERIE 116

118BISF

AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 150mm ean 18336

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Polyamide, Stainless steel

EAN13:8018793183369 **EAN5:**18336 **Article code:**05118SF1503FN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 200 DaN
Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------|
| Diameter (mm) | 150 |
| Band width (mm) | 40 |
| Hub width (mm) | 50 |
| Hub version | Plain bore |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 200 |
| Colour | White |
| Material | Polyamide 6 |
| Box pieces | / |
| Hardness scale | Shore D |
| Hardness | 82 |

Support data

| | |
|----------------------------|------------------|
| Plate size (mm) | 140X110 |
| Plate hole spacing (mm) | 105X080 |
| Plate hole size (mm) | 11X16 |
| Offset (mm) | 45 |
| Ground clearance (mm) | 181 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 250 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Rear |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |