

SERIE 116

# 118BIS

AVO - Wheel with polyamide 6 and steel castor for industry,  
diameter 150mm ean 20302

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled whit central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Polyamide, Stainless steel

**EAN13:**8018793203029    **EAN5:**20302    **Article code:**05118S01501RN



## Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 200 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore D    **Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

## Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	45
Ground clearance (mm)	181
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized