

SERIE 116N

97B

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 150mm ean 26629

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13:8018793266291 **EAN5:**26629 **Article code:**5118B01500RNN



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 400 DaN

- Concrete
- Stoneware

Rotation: Roller bearing

Hardness scale: Shore D

Hardness: 82

Flooring

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	400
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	50
Ground clearance (mm)	184
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized