

SERIE 116N-P

126A-N

AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 150mm ean 27825

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Heavy monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Polyamide

EAN13:8018793278256 **EAN5:**27825 **Article code:**05126NA0150CN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 500 DaN

Rotation: Ball bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	44
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	500
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13
Offset (mm)	/
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	630
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted