

SERIE 116-P

137A

AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 150mm ean 27844

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Heavy monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Polyamide

EAN13:8018793278447 **EAN5:**27844 **Article code:**05137A0150SCN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 1000 DaN
Rotation: Ball bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	55
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	1000
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	/
Ground clearance (mm)	270
Castor hole (mm)	/
Static load capacity (DaN)	2000
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted