Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 116

118BF

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 160mm ean 14668

Material: Polyamide 6 Core: Polyamide 6 Application field: Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled whit central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13:8018793146685 **EAN5**:14668 **Article code**:05118FB1600RN



Features

Minimum temperature: -25 Maximum temperature: 85 Dynamic load capacity: 420 DaN

Rotation: Roller bearing Hardness scale: Shore D Hardness: 82

Flooring

ConcreteStoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	420
Colour	White
Material	Polyamide 6
Box pieces	1
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	57
Ground clearance (mm)	209
Castor hole (mm)	1
Static load capacity (DaN)	530
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized