

SERIE 116N

## 97BF

AVO - Wheel with polyamide 6 and steel castor for industry,  
diameter 160mm ean 26675

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Polyamide, Stainless steel

**EAN13:**8018793266758    **EAN5:**26675    **Article code:**5118FB1600RNN



### Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 420 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore D    **Hardness:** 82

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	420
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

### Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	216
Castor hole (mm)	/
Static load capacity (DaN)	530
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized