

SERIE 116BU

# 118BF-BU

**AVO - Wheel with polyamide 6 and steel castor for industry, diameter 175mm ean 26391**

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Stainless steel, Polyamide

**EAN13:** 8018793263917    **EAN5:** 26391    **Article code:** 118FB1750RNB



## Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 475 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore D    **Hardness:** 82

## Flooring

- Concrete
- Stoneware

## Wheel data

Diameter (mm)	175
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	475
Colour	Blue
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	231
Castor hole (mm)	/
Static load capacity (DaN)	600
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized