

SERIE 116N

97

AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 175mm ean 26589

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13:8018793265898 **EAN5:**26589 **Article code:**5118001750CNN



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 475 DaN

- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore D

Hardness: 82

Flooring

Wheel data

Diameter (mm)	175
Band width (mm)	45
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	475
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	238
Castor hole (mm)	/
Static load capacity (DaN)	600
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized