

SERIE 116

118BISANT

AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 200mm ean 11273

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Stainless steel, Polyamide

EAN13: 8018793112734 **EAN5:** 11273 **Article code:** 05118S0A200RN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 300 DaN
Rotation: Roller bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	White
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized