Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 116BU

## 118BF-BU

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 200mm ean 26394

Material: Polyamide 6 Core: Polyamide 6 Application field: Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled whit central spacer.

**Heavy-Duty Castors:** 

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide



## **Features**

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 550 DaN

ConcreteStoneware

**Flooring** 

Rotation: Roller bearing

Hardness scale: Shore D

Hardness: 82

Wheel data

## Support data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	550
Colour	Blue
Material	Polyamide 6
Box pieces	1
Hardness scale	Shore D
Hardness	82

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	57
Ground clearance (mm)	244
Castor hole (mm)	1
Static load capacity (DaN)	690
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized