

SERIE 116N

## 97B

AVO - Wheel with polyamide 6 and steel castor for industry,  
diameter 200mm ean 26637

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

**Product line:** Stainless steel, Polyamide

**EAN13:**8018793266376    **EAN5:**26637    **Article code:**5118B02000RNN



### Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 550 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore D    **Hardness:** 82

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	550
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	244
Castor hole (mm)	/
Static load capacity (DaN)	690
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized