Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 116BU

118BF-BU

AVO - Wheel with polyamide 6 and steel castor for industry, diameter 80mm ean 26378

Material: Polyamide 6 Core: Polyamide 6 Scope: Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled whit central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13:8018793263788 **EAN5**:26378 **Article code**:118FB0800RNBU



Features

Minimum temperature: -25 Ma

Maximum temperature: 85

Dynamic load capacity: 150 DaN

ConcreteStoneware

Flooring

Rotation: Roller bearing

Hardness scale: Shore D

Hardness: 82

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	150
Colour	Blue
Material	Polyamide 6
Box pieces	1
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	1
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	36
Ground clearance (mm)	114
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized