

SERIE 116BU

118BF-BU

AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 80mm ean 26378

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Polyamide, Stainless steel

EAN13: 8018793263788 **EAN5:** 26378 **Article code:** 118FB0800RNBU



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 150 DaN
Rotation: Roller bearing **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Blue
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	36
Ground clearance (mm)	114
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized