

SERIE 116N

97

AVO - Wheel with polyamide 6 and steel castor for industry,
diameter 80mm ean 26566

Material: Polyamide 6 **Core:** Polyamide 6 **Application field:** Industry

Description:

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with self-locking nut.

Product line: Stainless steel, Polyamide

EAN13:8018793265669 **EAN5:**26566 **Article code:**5118000800FNN



Features

Minimum temperature: -25 **Maximum temperature:** 85 **Dynamic load capacity:** 150 DaN
Rotation: Plain bore **Hardness scale:** Shore D **Hardness:** 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	9X12
Offset (mm)	36
Ground clearance (mm)	118
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized