

SERIE 116N

## 97BF

AVO - Wheel with polyamide 6 and steel castor for industry,  
diameter 80mm ean 26663

**Material:** Polyamide 6    **Core:** Polyamide 6    **Application field:** Industry

**Description:**

Monolithic Polyamide 6 wheel. Hub on plain bore, roller bearings or shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Polyamide, Stainless steel

**EAN13:**8018793266635    **EAN5:**26663    **Article code:**5118FB0800CNN



### Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 150 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore D    **Hardness:** 82

### Flooring

- Concrete
- Stoneware

### Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	30
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	150
Colour	Black
Material	Polyamide 6
Box pieces	/
Hardness scale	Shore D
Hardness	82

### Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	9X12
Offset (mm)	36
Ground clearance (mm)	118
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized