

SERIE 116GR-CD

116GR-CD

AVO - Wheel with conductive polyamide for industry, diameter 120mm ean 28053

Material: Conductive Polyamide

Core: Conductive polyamide 6

Application field: Industry

Description:

Conductive Polyamide 6 wheel $R \leq 10000$ Ohm. Hub on roller bearings, shielded ball bearings assembled with central spacer, or plain bore.

Product line: Antistatic/Conductive

EAN13:8018793280532

EAN5:28053

Article code:G5116CD120GFP



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 150 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	120
Band width (mm)	20
Hub width (mm)	20
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	28X8
Dynamic load capacity (DaN)	150
Colour	Grey
Material	Conductive Polyamide
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/