

SERIE 116GR-PCD

116GR-PCD

AVO - Wheel with conductive polyamide for industry, diameter 125mm ean 28027

Material: Conductive Polyamide

Core: Conductive polyamide 6

Application field: Industry

Description:

Wheel with conductive Polyamide 6. Hub on roller bearings, shielded ball bearings assembled with central spacer, or plan bore.

Product line: Antistatic/Conductive

EAN13:8018793280273

EAN5:28027

Article code:05116CD101SCG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	42X12
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Conductive Polyamide
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/