

SERIE 116GR-CD

116GR-CD

AVO - Wheel with conductive polyamide for industry, diameter 125mm ean 28037

Material: Conductive Polyamide

Core: Conductive polyamide 6

Application field: Industry

Description:

Conductive Polyamide 6 wheel $R \leq 10000$ Ohm. Hub on roller bearings, shielded ball bearings assembled with central spacer, or plain bore.

Product line: Antistatic/Conductive

EAN13:8018793280372

EAN5:28037

Article code:G5116CD125GFP



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 210 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	210
Colour	Grey
Material	Conductive Polyamide
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/