

SERIE 116GR-PCD

## 116GR-PCD

AVO - Wheel with conductive polyamide for industry, diameter 150mm ean 25176

**Material:** Conductive Polyamide

**Core:** Conductive polyamide 6

**Application field:** Industry

**Description:**

Wheel with conductive Polyamide 6. Hub on roller bearings, shielded ball bearings assembled with central spacer, or plan bore.

**Product line:** Antistatic/Conductive

**EAN13:**8018793251761

**EAN5:**25176

**Article code:**05116CD150SCG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 400 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore D

**Hardness:** 82

### Flooring

- Concrete
- Stoneware

### Wheel data

|                             |                      |
|-----------------------------|----------------------|
| Diameter (mm)               | 150                  |
| Band width (mm)             | 50                   |
| Hub width (mm)              | 55                   |
| Hub version                 | Ball bearing         |
| Wheel hole (mm)             | 20                   |
| Bearing seat (mm)           | 47X14                |
| Dynamic load capacity (DaN) | 400                  |
| Colour                      | Grey                 |
| Material                    | Conductive Polyamide |
| Box pieces                  | /                    |
| Hardness scale              | Shore D              |
| Hardness                    | 82                   |

### Support data

|                            |   |
|----------------------------|---|
| Plate size (mm)            | / |
| Plate hole spacing (mm)    | / |
| Plate hole size (mm)       | / |
| Offset (mm)                | / |
| Ground clearance (mm)      | / |
| Castor hole (mm)           | / |
| Static load capacity (DaN) | / |
| Structure                  | / |
| Version                    | / |
| Brake                      | / |
| Plain axle                 | / |
| Stem type                  | / |
| Finishing                  | / |