

SERIE 116GR-CD

116GR-CD

AVO - Wheel with conductive polyamide for industry, diameter 175mm ean 23951

Material: Conductive Polyamide

Core: Conductive polyamide 6

Application field: Industry

Description:

Conductive Polyamide 6 wheel $R \leq 10000$ Ohm. Hub on roller bearings, shielded ball bearings assembled with central spacer, or plain bore.

Product line: Antistatic/Conductive

EAN13:8018793239516

EAN5:23951

Article code:G5116CD175GFP



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 475 DaN

Rotation: Plain bore

Hardness scale: Shore D

Hardness: 82

Flooring

- Concrete
- Stoneware

Wheel data

Diameter (mm)	175
Band width (mm)	50
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	475
Colour	Grey
Material	Conductive Polyamide
Box pieces	/
Hardness scale	Shore D
Hardness	82

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/